





Control options	ON-OFF	
Body finish	Matt white	Matt black
	Concrete grey	
CRI and CCT	CR185 3000K ⁽¹⁾ CR195 3000K	CR195 2700K CR195 4000K
Optics	Order separately	
Coloured ring	Coloured ring	
Ring Colour	Lacquered red	Matt orange
	Spring green	Corn yellow
	Matt white	Matt black
	Concrete grey	
Beam angle	Spot 21° Large 38°	Medium 28°
Accessory	Order separately	
Accessories	Narrow Optics 10° ⁽²⁾ Visor Satin diffuser	Cut-off Honeycomb louvre
Nominal Output	1700 lm	
Power	13W	
Ingress Protection Rating	IP20	
Insulation Class	Class I - Earth Connexion	
Energetic Class	Energy Class A+	
Flammable surfaces	Can be installed on normally flammable surfaces (90°)	
Distribution	Direct	
Weight	0.8 kg	

⁽¹⁾ Base version without designated code.

⁽²⁾ With this accessory there is no need to order coloured rings with optics


Notes The image of each product has a representative purpose



Product description

LED wall or ceiling luminaire with a single adjustable spotlight with proprietary joint allowing for 350° horizontal and +90°/-90° vertical adjustment. The body is manufactured from die-cast aluminium alloy 6060 with heat dissipating function. Wall fixings with nylon plugs. Optics available in Spot (29°), Medium (47°) and Large (53°). Optics come complete with a decorative ring that is available in seven liquid-coated finish options. The luminaire is available in matte white, matte black and concrete grey. Accessories include narrow optics attachment, honeycomb louvre and satin diffuser. Supplied in 3000K and CRI85 as standard. Available in CRI95, 2700K, 4000K. Ingress protection of IP20.


Photometric information



h (m)	Ø	Em (lux/klm)
h1	0,52	2467
h2	1,04	617
h3	1,57	274
h4	2,09	154
h5	2,61	99

PLURIEL PLUS


POWER	13W	13W	13W	13W
SOURCE CONSUMPTION	12,1W	12,1W	12,1W	12,1W
CRI	85	95	95	95
CCT (K)	3000	2700	3000	4000
NOMINAL FLUX (lm)	1679	1294	1361	1638
FIXTURE FLUX (lm)	1484	1144	1202	1447
EFFICIENCY (lm/W)	123	95	99	120



h (m)	Ø	Em (lux/klm)
h1	0,87	1490
h2	1,74	372
h3	2,61	166
h4	3,48	93
h5	4,35	60

PLURIEL PLUS

POWER	13W	13W	13W	13W
SOURCE CONSUMPTION	12,1W	12,1W	12,1W	12,1W
CRI	85	95	95	95
CCT (K)	3000	2700	3000	4000
NOMINAL FLUX (lm)	1679	1294	1361	1638
FIXTURE FLUX (lm)	1487	1146	1205	1450
EFFICIENCY (lm/W)	123	95	100	120




h (m)	Ø	Em (lux/klm)
h1	1,00	1310
h2	2,00	327
h3	3,01	146
h4	4,01	82
h5	5,01	52

PLURIEL PLUS

POWER	13W	13W	13W	13W
SOURCE CONSUMPTION	12,1W	12,1W	12,1W	12,1W
CRI	85	95	95	95
CCT (K)	3000	2700	3000	4000
NOMINAL FLUX (lm)	1679	1294	1361	1638
FIXTURE FLUX (lm)	1491	1149	1208	1459
EFFICIENCY (lm/W)	123	95	100	120

Accessories

9Q31252-Narrow Optics 10°




Matt black. With this accessory there is no need to order coloured rings with optics

9G040-Cut-off




Thanks to this accessory it is possible to obtain a narrow and sharp beam, with a greater contrast between the illuminated and nonilluminated area.

9G039-Visor



Thanks to this accessory it is possible to obtain an asymmetrically narrower and sharper beam with a greater contrast between the illuminated and non-illuminated area.

9G025-Honeycomb louvre



The accessory consists of a protective screen and black honeycomb grid.

9G026-Satin diffuser

