

LED RUNNER

LED RUNNER_ projectors



LED RUNNER **quick-lock rotation block_** **high efficiency COB LED source_**

Linear LED Projector for Unitrack fitted with three-way track adapter and quick-lock rotation block. Manufactured from extruded aluminium alloy 6060. 350° horizontal adjustment for the 14W version only.

Liquid painted finish options include matt white, matt black and anodised grey. Fitted with microscopic polycarbonate optics. Also available in DALI and 1-10V dimming options. Ingress protection of IP40.

INFO

Power

14/28W

Source

COB LED

Built to last

Lumen maintenance of 60000 hrs at L80B10.

Colour and Colour Temperature


CRI 85 - 2700K / CRI 85 - 3000K / CRI 85 - 4000K

Control


ON-OFF / DALI / 1-10V

Body finish

○ ● ●



LED RUNNER




LED RUNNER_ projectors

Product configurator

708 50


Code Control Source Finish CRI - CCT*

* For the version CRI 85 - 3000K it is not necessary to fill in the field.




LED RUNNER 290

Code	Kg	Control	Source	Finish	CRI - CCT
708	0,54	E0 ON-OFF	50 LED - 14W	42 ○ matt white	/8527 85 - 2700K
		EB 1-10V		52 ● matt black	- 85 - 3000K
		EE DALI		80 ● anodized grey	/8540 85 - 4000K



LED RUNNER 570

Code	Kg	Control	Source	Finish	CRI - CCT
708	0,95	E1 ON-OFF	50 LED - 28W	42 ○ matt white	/8527 85 - 2700K
		EP 1-10V		52 ● matt black	- 85 - 3000K
		EQ DALI		80 ● anodized grey	/8540 85 - 4000K



LED Runner

Power	Source consumption	CRI - CCT	Nominal	Deliv. output	Efficacy
14W	13,3W	85 - 2700K	1470 lm	E137 838 lm	72 lm/W
	11,7W	85 - 3000K	1630 lm	E137 929 lm	70 lm/W
	11,7W	85 - 4000K	1625 lm	E137 926 lm	79 lm/W
28W	26,6W	85 - 2700K	2940 lm	E137 1696 lm	72 lm/W
	23,4W	85 - 3000K	3260 lm	E137 1881 lm	71 lm/W
	23,4W	85 - 4000K	3250 lm	E137 1875 lm	80 lm/W

